

## micro line

### MLC-300

2xDVB-S/S2/T/T2/C + 2xFlexCAM to 4xDVB-T/C + IP



#### Features

- 2 x independent multi-standard inputs DVB-S/S2/T/T2/C
- 2 x FlexCAM
- 4 x RF output DVB-T/C (software selectable)
- Gbit IP streaming (up to 64 x SPTS / 4 x MPTS)
- "Pool" technology
- MER value > 42dB
- PID filtering
- Dual power supplies offering redundancy mode
- Custom NIT/SDT
- Local or remote control via webserver
- Very friendly user interface
- Wall or rack mount options
- SNMP v2
- Ultra-compact size
- 5-year warranty

[www.lemco.tv](http://www.lemco.tv)



# MLC-300

**2xDVB-S/S2/T/T2/C + 2xFlexCAM to 4xDVB-T/C + IP**



- ◆ The MLC-300 is a very powerful, all-in-one mini headend device, able to receive up to 2 independent satellite (DVB-S/S2), terrestrial (DVB-T/T2) or cable (DVB-C) signals with 2x CI interfaces and convert them either in 4 x DVB-T/C RF output channels or in IPTV streaming using UDP/RTP protocols multicast/unicast.
- ◆ It supports "pool" technology, meaning that the user is able to select any program from any of the 2 inputs and assign them to any of the 4 RF or IP outputs providing great flexibility. The FlexCAM technology provides the ability to the user to connect the CAMs either at the inputs or the outputs of the device.
- ◆ The embedded web server of the MLC-300 provides a very friendly user interface as well as the ability of remote or local control of the device via LAN.
- ◆ Its small size and its powerful features render the MLC-300 the ideal solution in case we want to distribute FTA (Free-To-Air) or scrambled TV programs coming from satellite (DVB-S/S2), terrestrial (DVB-T/T2) or cable (DVB-C) sources to a CATV installation using the DVB-T/C or IPTV technology.

## Technical Specifications

Input	
Type	2 x DVB-S/S2/T/T2/C
Frequencies	950...2150 MHz DVB-S/S2 118...900 MHz DVB-T/T2/C
Connector	75Ω - F, female
Descrambling	Yes, Accepts 2 x universal CAM capable of connecting either on input or output
<b>LNB</b>	
Voltage	OFF / 13V / 18V
Current	Less than 400mA
22 kHz signal	On / Off
22 kHz signal - Voltage	0.65V ±0.35V
22 kHz signal - Frequency	22 KHz ±4Hz
22 kHz signal - DiSEqC	1.0 (Port A, B, C, D)
<b>DVB-S (IN)</b>	
Symbol rate	1 - 45 MBaud
Roll off factor	0.2, 0.25, 0.35
Code rate	1/2, 2/3, 3/4, 5/6, 7/8 (Automatic)
Spectral inversion	Reverse, Non-reverse (Automatic)
<b>DVB-S2 (IN)</b>	
Constellation	QPSK, 8PSK (Automatic)
Symbol rate	1 - 55 MBaud (QPSK) 1 - 45 MBaud (8PSK)
Roll off factor	0.2, 0.25, 0.35 (Automatic)
Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 8/10 (QPSK-Automatic) 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 (8PSK-Automatic)
Spectral inversion	Reverse, Non-reverse (Automatic)
<b>DVB-T (IN)</b>	
Bandwidth	6, 7, 8 MHz
Mode	2K, 8K
Constellation	QPSK, 16QAM, 64QAM
Guard interval	1/4, 1/8, 1/16, 1/32
Code rate	1/2, 2/3, 3/4, 5/6, 7/8
<b>DVB-T2 (IN)</b>	
Bandwidth	5, 6, 7, 8 MHz
Mode	1K, 2K, 4K, 8K, 16K, 32K (Included extended mode)
Constellation	QPSK, 16QAM, 64QAM, 256QAM
Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6
<b>DVB-C (Annex A,B,C) (IN)</b>	
Bandwidth	5, 6, 7, 8 MHz
Mode	Automatic modulation detection
Constellation	16QAM, 32QAM, 64QAM, 128QAM, 256QAM
<b>Transport Stream Processing</b>	
Services	User selection by service names
Automatic regeneration	PAT, CAT, SDT, PMTs, EITs tables
NIT	Pass-through, custom,automatic
PCR	re-stamping
LCN support	Yes

RF Output	
Type	4 x RF out in adjacent channels
Output Frequencies	110...950 MHz (1 Hz step)
Output Level	90dBuV
Connector	75Ω - F, female
Output Attenuator	0...-20dB
MER	More than 42dB
<b>DVB-T (OUT)</b>	
Bandwidth	5, 6, 7, 8 MHz
Mode	2K, 8K
Constellation	QPSK, 16QAM, 64QAM
Guard interval	1/4, 1/8, 1/16, 1/32
Code rate	1/2, 2/3, 3/4, 5/6, 7/8
<b>DVB-C (OUT)</b>	
Bandwidth	5, 6, 7, 8 MHz
Mode	2K, 8K
Constellation	16QAM, 32QAM, 64QAM, 128QAM, 256QAM
Symbol rate	1-7.2 Ms/s
<b>IP Streaming</b>	
IP TS Out	Yes
Protocol	UDP / RTP (Multicast/Unicast)
Speed	1 Gbit
IGMP support	Yes, v2, v3
Type	MPTS (up to 4 TS) SPTS (up to 64TS)
Max. bitrate	480Mbps max.
<b>Programming Interface</b>	
Ethernet webserver	Yes, embedded webserver
Speed	10/100 Mbps
Connector	RJ45
Browser compatibility	Chrome, Firefox, Safari, Opera, Edge et al.
<b>General</b>	
Power supply	2 x +12VDC
Power supply consumption	1.8A max.
Operating temperature	0 °C to 40 °C
Storage temperature	-10 °C to +70 °C
Humidity	Up to 90%
Dimensions	235 x 115 x 48 mm
Weight	450 g



**LEMCO®**  
DIGITAL TV SOLUTIONS